

# Technical data sheet

## Cable tie, black, UV and weather-resistant

Item number: 2331862



Cable ties are used for quick, uncomplicated fixing or bundling of cables and pipes to cable support systems or other mounting structures.




PA Polyamide

### Master data

Item number	2331862
Type	565 4.8x120 SWUV
Description 1	Cable ties
Description 2	UV-resistant
Manufacturer	OBO
Dimension	4.8x120mm
Colour	Black
Material	Polyamide
Smallest sales unit	100
Unit of quantity	Piece
Weight	0.089 kg
Weight unit	kg/100 pc.

### Dimensions



Length	120 mm
Width	4.8 mm
Height	1.5 mm
Dimension B	4.8 mm
Dimension L	120 mm
Dimension t	1.5 mm

# Technical data sheet

Cable tie, black, UV and weather-resistant

Item number: 2331862



## Technical data

Version for	Externally toothed
Strip closure	Plastic tongue/tab
Fastening type	Without
Labelling area	Without
Halogen-free	yes
Releasable lock	no
Max. Bundle diameter	27 mm
MIL approval	no
Mounting temperature, max.	90 °C
Mounting temperature_min.	-30 °C
Reflective	no
Permitted temperature range, max.	90 °C
Permitted temperature range, min.	-30 °C
Transparent	no
UL approval	yes
UV-resistant	yes
VG approval	no
Tensile strength	220 N