## **Technical data sheet** Drop-in anchor E A4

### Item number: 3492922




Drop-in anchor for single fixings of non-load-bearing systems in non-cracked concrete as well as for multiple fixings in cracked and non-cracked concrete.

Tested to fire protection standards, fire resistance class R 120 according to European Technical Approval ETA-02/0020 (option 7) and European Technical Approval ETA-05/0116.

Mounting with marking and setting tool.



## CE



#### Master data

| Item number         | 3492922          |
|---------------------|------------------|
| Туре                | E M 10x40 A4     |
| Description 1       | Drop-in anchor E |
| Manufacturer        | OBO              |
| Dimension           | M10x40           |
| Material            | Stainless steel  |
| Surface             | Bright, treated  |
| Surface standard    |                  |
| Smallest sales unit | 50               |
| Unit of quantity    | Piece            |
| Weight              | 2.16 kg          |
| Weight unit         | kg/100 pc.       |

# Technical data sheet Drop-in anchor E A4

## Item number: 3492922



| Dimensions     |   |                |                  |
|----------------|---|----------------|------------------|
|                |   | Length         | 40 mm            |
| ◆ E M10        |   | Dimension L    | 40 mm            |
|                |   |                |                  |
|                |   |                |                  |
|                |   |                |                  |
|                | L |                |                  |
|                |   |                |                  |
| 1              |   |                |                  |
| Technical data | a |                |                  |
|                |   | Version for    | Lightning strike |
|                |   | Fastening unit | Miscellaneous    |

| Version for                       | Lightning strike |
|-----------------------------------|------------------|
| Fastening unit                    | Miscellaneous    |
| Drill hole depth                  | 40 mm            |
| Drill hole diameter, min.         | 12 mm            |
| Screw-in depth, max.              | 15 mm            |
| Screw-in depth, min.              | 11 mm            |
| Thread                            | M10              |
| Thread metric                     | 10               |
| Self-drilling                     | no               |
| Approvals available               | yes              |
| Permitted load range, tension zo- | 2                |
| ne                                |                  |