Technical data sheet Drop-in anchor E A4

Item number: 3492912




Drop-in anchor for single fixings of non-load-bearing systems in non-cracked concrete as well as for multiple fixings in cracked and non-cracked concrete.

Tested to fire protection standards, fire resistance class R 120 according to European Technical Approval ETA-02/0020 (option 7) and European Technical Approval ETA-05/0116.

Mounting with marking and setting tool.



CE



Master data

| Item number | 3492912 |
|---------------------|------------------|
| Туре | E M 8x40 A4 |
| Description 1 | Drop-in anchor E |
| Manufacturer | OBO |
| Dimension | M8x40 |
| Material | Stainless steel |
| Surface | Bright, treated |
| Surface standard | |
| Smallest sales unit | 50 |
| Unit of quantity | Piece |
| Weight | 1.49 kg |
| Weight unit | kg/100 pc. |

Technical data sheet Drop-in anchor E A4

Item number: 3492912



| Dimensions | | | | |
|----------------|---|----------------|------------------|--|
| ♦ E M10 | | Length | 40 mm | |
| | | Dimension L | 40 mm | |
| | | | | |
| | | | | |
| | _ | | | |
| | L | | | |
| | | | | |
| Technical data | | | | |
| | | Version for | Lightning strike | |
| | | Eastoning unit | Miccollapoous | |

| Version for | Lightning strike |
|---|------------------|
| Fastening unit | Miscellaneous |
| Drill hole depth | 40 mm |
| Drill hole diameter, min. | 10 mm |
| Screw-in depth, max. | 20 mm |
| Screw-in depth, min. | 9 mm |
| Thread | M8 |
| Thread metric | 8 |
| Self-drilling | no |
| Approvals available | yes |
| Permitted load range, tension zo- ne | 2 |