

Technical data sheet

Mesh cable tray connector, long FS

Item number: 6016680



Long mesh cable tray connectors for screwless straight connection of mesh cable trays.

Two straight connectors, type GRV 245, are used for each connection point.

Can be used from a mesh cable tray width of 100 mm.

The FS variant is used to connect electrogalvanised mesh cable trays, the DD variant to connect hot/hot-dip galvanised mesh cable trays and the VA variant to connect stainless steel mesh cable trays.



St Steel

FS Strip galvanized

Master data

| | |
|---------------------|--------------------------------|
| Item number | 6016680 |
| Type | GRV 245 FS |
| Description 1 | Quick connector |
| Description 2 | for mesh cable tray, long type |
| Manufacturer | OBO |
| Dimension | L245mm |
| Material | Steel |
| Surface | Strip galvanized |
| Surface standard | DIN EN 10346 |
| Smallest sales unit | 20 |
| Unit of quantity | Piece |
| Weight | 13.5 kg |
| Weight unit | kg/100 pc. |

Technical data sheet

Mesh cable tray connector, long FS

Item number: 6016680



Dimensions



| | |
|-----------------|----------|
| Dimension | 245 x 30 |
| Length | 245 mm |
| Width | 30 mm |
| Width | 1.18 in |
| Height | 14 mm |
| Height | 0.55 in |
| Plate thickness | 2 mm |

Technical data

| | |
|----------------------------------|---------------------|
| Version for | Straight connector |
| Maintain electrical functions | no |
| Suitable for mesh cable tray | yes |
| Suitable for cable ladder | no |
| Suitable for cable tray | no |
| Adjustable connector, horizontal | no |
| Articulated connector, vertical | no |
| Rustproof steel, pickled | no |
| Connection type | Screwless connector |