Technical data sheet

Distribution box, 5 division units, with terminal strip, polystyrene

Item number: 2008804





Distribution box with terminal strip for surface mounting, for the current sub-distribution in interior and protected exterior areas, in accordance with IEC 439-3. With pre-mounted 35 mm hat profile rail. IP66 protection type and IK07 protection rating. Transparent cover to screw on, with cut-out.

- Protection-insulated for a maximum of 5 division units
- Terminal strip set consisting of: One each of: PE/N terminal with 4x 16 mm² screw terminals, mini hat profile rail, mounting instructions and fastening set
- Identification plates for connected consumers
- 4 elastic cable entries Ø20 mm for cable diameters of 0-17 mm
- 1 elastic cable entry Ø25 mm for cable diameters of 0-22 mm
- 4 $\ensuremath{\text{\varnothing}}$ 20 mm break-out openings each at the top and bottom
- 1 Ø 20/25 mm combination break-out opening each at the top and bottom
- 4 screw cover caps Nominal current 40 A Power loss at 40 K 19 W

















Polystyrene

Master data

Item number	2008804
Type	SDB 05 PS
Description 1	Small distributor
Description 2	for max. 5 distribution units
Manufacturer	OBO
Dimension	190x150x125
Colour	Light grey; RAL 7035
Material	Polystyrene
Smallest sales unit	1
Unit of quantity	Piece
Weight	81.5 kg
Weight unit	kg/100 pc.

Dimensions

Length	191 mm
Width	151 mm
Height	126 mm

Technical data sheet

Distribution box, 5 division units, with terminal strip, polystyrene

Item number: 2008804



Technical data Extension option yes Number of rows Cover type Cover Version, small distributor cover With cut-out DIN rail yes Installation location Internal EMC version Glow wire test 650 °C Terminals Connector With mounting plate no With lock no Mounting type, consumer units Structure Nominal insulating voltage AC 1000 V 1500 V Nominal insulating voltage DC Nominal voltage 400 V Nominal current 40 A Protection rating IP66

IK07.

yes

Protection rating IK code

Transparent lid