Technical data sheet Junction box T 350, closed

Item number: 2007303





Closed junction box for the connection of cables and lines indoors and in protected outdoor areas. Rectangular design without entries. Suitable for wall and ceiling mounting, on mounting panels and threads in the floor. With the option to fasten inside and to mount via the corner domes. Cover with quick lock, sealable. Made from halogen-free and UV-resistant materials.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650 °C. Impact resistance IK05 according to DIN EN 50102.





Polypropylene, fibreglass reinforced


Master data

Item number2007303TypeT 350 OEDescription 1Junction boxDescription 2without insertion openingManufacturerOBODimension285x201x120ColourLight grey; RAL 7035MaterialPolypropylene, fibreglass reinforcedSmallest sales unit1Unit of quantityPiece		
Description 1Junction boxDescription 2without insertion openingManufacturerOBODimension285x201x120ColourLight grey; RAL 7035MaterialPolypropylene, fibreglass reinforcedSmallest sales unit1	Item number	2007303
Description 2without insertion openingManufacturerOBODimension285x201x120ColourLight grey; RAL 7035MaterialPolypropylene, fibreglass reinforcedSmallest sales unit1	Туре	T 350 OE
ManufacturerOBODimension285x201x120ColourLight grey; RAL 7035MaterialPolypropylene, fibreglass reinforcedSmallest sales unit1	Description 1	Junction box
Dimension 285x201x120 Colour Light grey; RAL 7035 Material Polypropylene, fibreglass reinforced Smallest sales unit 1	Description 2	without insertion opening
Colour Light grey; RAL 7035 Material Polypropylene, fibreglass reinforced Smallest sales unit 1	Manufacturer	OBO
Material Polypropylene, fibreglass reinforced Smallest sales unit 1	Dimension	285x201x120
Smallest sales unit 1	Colour	Light grey; RAL 7035
	Material	Polypropylene, fibreglass reinforced
Unit of guantity Piece	Smallest sales unit	1
	Unit of quantity	Piece
Weight 58.8 kg	Weight	58.8 kg
Weight unit kg/100 pc.	Weight unit	kg/100 pc.

Technical data sheet Junction box T 350, closed

Item number: 2007303





Technical data

Expandable	yes
Type of insertion	None
Type of entry	Cable
Type of housing penetration	Without
Measured insulation voltage Vi	500 V
Equipment	Without
Cover	Not transparent
Cover fastening	Screwed
Entry from rear	yes
Entries	None
Explosion-tested version	no
Flame-resistant	Acc. to VDE 0471/DIN 695 Part 2-1, test temperature 750°C
Shape	Rectangular
Maintain electrical functions	Without
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without
Fibre-glass reinforced	yes
Halogen-free	yes
Clear internal dimensions	267x182x110 mm
With screening	no
with lid	yes
Mounting type	Wall/ceiling mounting
Nominal cross-section, min.	35 mm ²
Nominal voltage	500 V
Sealable	yes
Protection rating	IP66
Protection rating IK code	IK05.
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C
Weatherproof	no

Technical data sheet

Junction box T 350, closed

Item number: 2007303

