## **Technical data sheet**

UDHOME-ONE floor socket, without floor covering recess, BS socket, stainless steel Item number: 7368306





Square floor socket for use in dry-care systems and screed floors in indoor areas. Installation housing with pre-marked insertion openings for pipes (M20/M25). Cover adjustable to top edge of floor covering using four height-adjustment supports. The minimum installation depth is 75 mm, the height-adjustment range +30 mm. Frame and cover made of stainless steel and visible in the floor covering. Cover with decorative plate. The load-bearing capacity of 15 kN is only guaranteed when in an unused state. The delivery includes a switched BS socket.




## Master data

Item number	7368306
Туре	UDHOME-ONE V BS
Description 1	Floor socket
Description 2	with BS socket, decor lid
Manufacturer	OBO
Dimension	140x140x75
Material	Stainless steel
Smallest sales unit	1
Unit of quantity	Piece
Weight	199 kg
Weight unit	kg/100 pc.

## **Technical data sheet**

UDHOME-ONE floor socket, without floor covering recess, BS socket, stainless steel Item number: 7368306





Equipment	Single BS socket
Floor covering protection frame	no
Floor care	Dry
Cover version	Decorative plate
Seal installation option	no
Application when used	6.101.1 Dry floor care
Application when unused	6.101.1 Dry floor care
Floor height, max.	105 mm
Floor height, min.	75 mm
Suitable for raised floor installation	yes
Suitable for screed-flush closed underfloor ducts	no
Suitable for screed-covered un- derfloor ducts	no
Suitable for cavity floor installation	yes
Suitable for wet care	no
Suitable for underfloor ducts	no
Device support to accept moun- ting boxes	no
With floor covering recess	no
Protection rating (IP) when used	IP20
Protection rating (IP) when unu- sed	IP40
Protection rating IK code	IK10
Heavy-duty version	no
Vertical load, large area	to 15,000 N

## **Technical data sheet**

UDHOME-ONE floor socket, without floor covering recess, BS socket, stainless steel Item number: 7368306



**Technical data** 

Vertical load, small area Opening mechanism to 3,000 N Handle