Technical data sheet Junction box X 02

Item number: 2005054





Junction box for the connection of cables in indoor and outdoor areas. Square design with knock-out entries. Suitable for wall and ceiling mounting with the option to fasten outside, inside or to mount via the corner domes. Particularly impact resistant with IK09. Transparent cover with quick lock, sealable. Made from halogen-free and UV-resistant materials.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650°C. Impact resistance IK09 according to DIN EN 50102. Protection rating IP67 according to DIN EN 60529.

























Polycarbonate

Master data		
	Item number	2005054
	Туре	X02 LGR-TR
	Description 1	Junction box
	Description 2	with transparent lid
	Manufacturer	ОВО
	Dimension	95x95x72
	Colour	Grey / transparent
	Material	Polycarbonate
	Smallest sales unit	1
	Unit of quantity	Piece
	Weight	17.8 kg
	Weight unit	kg/100 pc.

Technical data sheet


Junction box X 02

Item number: 2005054



Dimensions 22

Length	95 mm
Width	95 mm
Height	72 mm



Technical data

Expandable yes No. of entries 7 Type of entry Cuttable stepped membrane Type of housing penetration Pre-marking		
Type of entry Cuttable stepped membrane		
Type of housing penetration Pre-marking		
Measured insulation voltage Vi 750 V		
Equipment Without		
Cover Not transparent		
Cover fastening Screwed	Screwed	
Entry from rear no		
Entries 7 x Ø20		
Explosion-tested version no		
Flame-resistant acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C		
Shape Square		
Fibre-glass reinforced yes		
Halogen-free yes		
Clear internal dimensions 85x85x57 mm	85x85x57 mm	
Max. Conductor cross-section 2.5 mm ²		
With screening no		
with lid yes		
Mounting type Wall/ceiling mounting		
Nominal cross-section, max. 2.5 mm ²		
Nominal cross-section, min. 1 mm ²		
Nominal voltage 750 V		
Sealable yes		
Impact-resistant yes		

Technical data sheet Junction box X 02



Item number: 2005054

Technical data		
	Protection rating	IP67
	Protection rating IK code	IK09
	Permitted temperature range, max.	60 °C
	Permitted temperature range, min.	-5 °C
	Weatherproof	yes